Attorney Docket No. M-1007-9C US
EXPRESS MAIL LABEL NO. EL 710 215 005 US

FIELD PROGRAMMABLE PRINTED CIRCUIT BOARD

Amr M. Mohsen

FIELD OF THE INVENTION

This invention relates to printed circuit boards and in particular to a printed circuit board which is programmable in the field by the designer of an electronic system to provide a desired function and to the method of programming the programmable printed circuit board of this invention.

BACKGROUND OF THE INVENTION

Printed circuit boards are commonly used in electronic devices such as instruments, computers, telecommunication equipment and consumer electronic products. Typically, an engineer will design a printed circuit board to carry the types of components necessary to implement the desired electronic function and to fit in the space available for the board. Consequently, each printed circuit board typically is custom designed. To design a custom printed circuit board is expensive, takes time and requires the fabrication of prototype printed circuit boards. If errors are found in the prototypes, then the printed circuit board must be redesigned. Such a process often delays the planned introduction of a new product.

SUMMARY OF THE INVENTION

In accordance with this invention, a printed circuit board of unique configuration is combined with one or more special programmable integrated circuit chips (hereinafter called "programmable interconnect chips" or "PICs") to provide a user programmable printed circuit board capable of being used to provide any one of a plurality of functions.

In one embodiment of the invention, a field programmable printed circuit board comprises

(1) a multiplicity of component contacts for receipt of the leads of electronic components;

(2) a corresponding multiplicity of PIC contacts

for receipt of the leads on the package or packages of the programmable interconnect chip or chips; and

(3) one or more layers of conductive traces, each conductive trace uniquely connecting one component contact to one PIC contact.

Typically, electronic components comprise integrated circuits and/or discrete devices contained, respectively, in standard integrated circuit or discrete device packages and in addition, discrete elements which include resistors, capacitors and inductors, for example.

Generally the component contacts and PIC contacts comprise holes in the printed circuit board, the interior surfaces of which are plated to a selected thickness with a conductive material such as copper. Alternatively, these contacts are pads or any other structure for electrically and physically joining electronic components and integrated circuits to a printed circuit board. Advantageously, the PIC contacts are usually (though not necessarily) smaller than the component contacts so that the area of the programmable printed circuit board occupied by the programmable interconnect chip or chips is much smaller than the area of the printed circuit board occupied by the electronic components. Each PIC contact brings a corresponding trace from a selected level on the PC board to the surface of the PC board so that trace is then connectable to a pin or electrical contact on a programmable interconnect chip. For every component contact (the function of which is to receive the pin or electrical contact of an electronic component) there is a corresponding electrically conductive trace which interconnects that component contact to a corresponding PIC contact (the function of which is to receive the pin or electrical contact of the programmable interconnect chip) in the printed circuit board. Thus, each component contact is electrically and uniquely connected to a corresponding PIC contact for electrically contacting a programmable interconnect chip of this invention.

In accordance with this invention more than one

programmable interconnect chip is, if desired, placed on a printed circuit board to provide enhanced interconnection flexibility and cost optimization for the electronic components on the printed circuit board. Such a board then has additional PIC contacts corresponding to and for connection to the external pins or electrical contacts on the additional packages containing the additional programmable interconnect chips.

The field programmable printed circuit board (hereinafter sometimes referred to as a "FPPCB") of this invention substantially reduces the cost associated with developing complex electronic systems by providing a standard PC board configuration which is easily and economically manufactured. In accordance with this invention, the designer of electronic systems utilizing the standard programmable PC board of this invention will also utilize computer aided design software to determine the optimum placement of the electronic components on the programmable PC board and to determine the configuration of the programmable interconnect chip or chips of this invention to properly interconnect the electronic components so as to yield the desired electronic system.

In accordance with the method of this invention a user designing an electronic system utilizing the programmable PC board of this invention will first place a model of the programmable PC board in the computer aided design system. The user then will simulate the placement of models of the desired electronic components, be they discrete elements, memory, logic gates, or microprocessors, on selected component contacts on the programmable PC board and will simulate the interconnection of these electronic components using the standard PC board of this invention together with the programmable interconnect chip or chips of this invention. The computer will then simulate the electrical performance of the system with the electrical components so placed and interconnected and will indicate whether or not the configuration selected by the designer yields the desired electronic function. The designer will have choices

in the placement of the electronic components on the programmable PC board and in their interconnection but will be assisted in this placement by certain logical rules contained in the computer aided design program. Algorithms for use in computer aided design systems of the type required to implement the design of electronic systems utilizing the programmable PC board and programmable interconnect chip of this invention are of a type currently available in the electronic design industry.

The programmable printed circuit board of this invention is considered to be "field programmable" because the designer of an electronic system is able to program the placement of electronic components on the unique PC board of this invention by using and configuring the programmable interconnect chips of this invention. The PC board of this invention is unique in that it has a standard configuration regardless of the electronic function to be implemented and thus is relatively inexpensive and easy to make. At the same time, the field programmable PC board of this invention is programmable by use of one or more programmable interconnect chips.

In an alternative embodiment of this invention, the programmable PC board of this invention includes on a portion of its surface electronic components which are interconnected using custom designed interconnections to form a particular circuit function. Conductive traces transmit the signals from this custom portion of the PC board to one or more programmable interconnect chips on the remainder of the PC board. The programmable interconnect chip or chips are configured by the user to achieve the desired function required utilizing both the custom portion of the PC board and the programmable portion of the PC board.

Throughout this specification, the field programmable PC board of this invention will usually be described as having component holes and PIC holes for receipt of the electrical leads of the electronic components and of the programmable interconnect chip, respectively. The term

"component hole" and the term "PIC hole" will be used to describe a standard hole formed in a PC board and plated with a conductive material as in the prior art to receive a conductive lead. However, any conductive structure capable of being used to electrically contact and physically hold the package of an electronic component can be used in place of a component hole or a PIC hole. Such a structure includes a solder pad and a socketed printed circuit board opening for slidably receiving and releasing the pins of an electronic component package. It should be noted that the term PIC hole is used to distinguish the function of certain holes in the programmable printed circuit board of this invention from the component holes. However, both types of holes are plated with a conductive material and have the same purpose -- that is to electrically transmit signals from either the pin of the package of an electronic component to a conductive trace or from a conductive trace to the pin of an electronic component or through the programmable interconnect chip to another trace or from a conductive trace to another conductive trace.

In certain circumstances, a PIC hole or a component hole can be used to interconnect two traces directly. Such a configuration occurs in custom designed PC boards.

This invention will be more fully understood in conjunction with the following detailed description together with the attached drawings.

DESCRIPTION OF THE DRAWINGS

Figure 1a illustrates in isometric view a programmable printed circuit board of this invention containing a plurality of layers of traces such as trace 103-r,c each trace connecting uniquely one component hole 102-r,c to a corresponding PIC hole 104-r,c (shown in Figure 1b);

Figure 1b illustrates an isometric view of the portion of the programmable PC board 100 of Figure 1a beneath programmable interconnect chip 105 containing the PIC holes (such as hole 104-r,c) for connection of the traces (such as trace 103-r,c) to the pins or electrical contacts on the

programmable interconnect chip 105 of this invention;

Figures 2a through 2d illustrate schematically four top plan views of printed circuit board 100 utilizing the programmable interconnect chip 105 of this invention together with the multiplicity of component holes 102-1,1 through 102-R,C (not shown) arranged on the printed circuit board together with a schematic representation of conductive busses 103 each bus containing a plurality of conductive traces such as traces 103-1,1 through 103-1,3 for interconnecting each of the component holes 102 to a corresponding PIC hole 104 beneath the programmable interconnect chip 105;

Figures 3a, 3b, 3c and 3d illustrate a number of different global interconnect architectures suitable for use with this invention;

Figures 4a and 4b illustrate respectively the top and side views of a programmable printed circuit board 400 constructed in accordance with this invention together with a programmable interconnect chip 405 placed on the board to interconnect the electronic components to be placed on the PC board 400 in a selected manner to provide the desired electronic function;

Figure 5 illustrates a programmable printed circuit board 500 of this invention containing a testport and a control port for testing the state of each trace on the programmable printed circuit board 500 and for configuring the programmable interconnect chip 505 to interconnect in the desired manner the electronic components 506-1 through 506-4 placed on the PC board 500;

Figures 6a through 6e illustrate a number of structures for implementing the programmable interconnect chip 605 suitable for use in implementing the programmable PC board of this invention;

Figure 7a illustrates the architecture of the programmable interconnect chip 605;

Figure 7b illustrates one structure for programming the intersection of two conductive leads formed on the programmable interconnect chip 605;

Figure 7c illustrates a bilateral circuit for controlling the transmittal of signals to or from a test port used in conjunction with the programmable interconnect chip 605 of this invention; and

Figures 8a and 8b illustrate structures for connecting electronic component packages and/or a package containing a programmable interconnect chip to the programmable printed circuit board of this invention.

DETAILED DESCRIPTION

The following description is meant to be illustrative only and not limiting. Other embodiments of this invention will be obvious to those skilled in the art in view of this description.

Figure 1 is an isometric cross-sectional view of the programmable printed circuit board of this invention. As shown in Figure 1, programmable PC board 100 comprises a plurality of layers 101-1 through 101-4 of insulating material. On each layer 101-i (where $1 \leq i \leq 4$) is formed a plurality of electrical traces 103. Formed in the printed circuit board are a multiplicity of component holes 102-1,1 through 102-R,C where R represents the number of component rows of holes formed on the programmable printed circuit board and C represents the number of columns of component holes formed on the board. Thus, the programmable printed circuit board illustrated in Figure 1a has rows of component holes 102-1,X through 102-R,X (where X is an integer which varies from 1 to C) and has columns of component holes 102-Y,1 through 102-Y,C where Y is an integer which varies from 1 to R. As shown in Figure 1a, traces 103-1,1 through 103-1,C, 103-2,1 through 103-2,C and 103-3,1 through 103-3,C are formed on the top surface of insulating layer 101-1. Traces 103-4,1 through 103-6,C (not shown) are formed on the top surface of layer 101-2. Traces 103-7,1, through 103-9,C (not shown) are formed on the top surface of layer 101-3 and traces 103-10,1 through 103-12,C are formed on the top surface of layer 101-4. Each trace 103-r,c (where r indicates the row and is given by $1 \leq r \leq R$ and c indicates

the column and is given by $1 \leq c \leq C$) interconnects a corresponding component hole 102-r,c to a corresponding PIC hole 104-r,c (shown in Figure 1b) connectable to a selected pin on programmable interconnect chip 105 (shown in Figure 1a).

In the description of Figure 1a, for simplicity not all component holes 102-r,c are actually numbered nor are all traces 103-r,c numbered. However, the numbering the component holes 102-r,c, traces 103-r,c and the PIC holes 104-r,c is consistent with each electrically connected component hole 102-r,c, trace 103-r,c and PIC hole 104-r,c all having the same indicia r,c.

Figure 1b illustrates PIC hole 104-r,c connected to trace 103-r,c so as to bring the electrical signal on trace 103-r,c to the top surface of layer 101-4 of the PC board 100 for electrical contact to the programmable interconnect chip (shown in Figure 1a but not in Figure 1b) of this invention. Figure 1b shows an isometric cutaway drawing of a portion of the programmable printed circuit board 100 of this invention with PIC holes 104-1,1 through 104-R,C (not shown) being arranged in a selected location on the printed circuit board 100 so as to bring to a portion of the top surface of insulating layer 101-4 of the printed circuit board 100 the electrical signals carried by traces 103-1,1 through 103-R,C. The PIC holes 104-1,1 through 104-R,C (each of which is plated on its interior surface with a conductive material) are arranged in a pattern on the printed circuit board so as to mate with the pins or other electrical connections on the package containing the programmable interconnect chip. Thus the area of the programmable PC board 100 occupied by PIC holes 104-1,1 through 104-R,C is desirably (though not necessarily) much smaller than the area of the printed circuit board occupied by component holes 102-1,1 through 102-R,C. The internal diameter of the PIC holes 104-1,1 to 104-R,C is much smaller than the internal diameter of the component holes 102-1,1 to 102-R,C and is only sufficient to allow the pins or other electrical connectors on the package of the programmable

interconnect chip to make proper electrical contact to traces 103-1,1 through 103-R,C.

Figure 2a illustrates in top view the local interconnect architecture of the programmable interconnect chip 105 mounted on the programmable printed circuit board 100 of this invention to show the conductive paths followed by the traces 103 interconnecting the component holes 102 to the PIC holes 104. Figure 2a illustrates the conductive traces on one layer 101-1 of PC board 100 only. Each layer of PC board 100 will have a similar pattern of traces. The regions under programmable interconnect chip 105 to which the traces are directed differ from level to level because each trace 103-r,c uniquely interconnects one component hole 102-r,c to a corresponding PIC hole 104-r,c. Figure 2b is similar to Figure 2a except it illustrates schematically the trace interconnect structure to interconnect component holes 102-r,c to PIC holes 104-r,c utilizing the traces 103-r,c on printed circuit board insulating layer 101-2. Note that the traces 103 on insulating layer 101-2 interconnect different component holes 102 than do the traces shown in Figure 2a. Similar drawings for the interconnect traces formed on insulating layers 101-3 and 101-4 are shown in Figures 2c and 2d illustrating the different component holes 102-r,c being connected to the PIC holes 104-r,c by the traces 103-r,c on the layers of insulation 101-3 and 101-4.

While Figures 2a through 2d illustrate a programmable printed circuit board 100 utilizing one programmable interconnect chip 105 of this invention, more than one programmable interconnect chip 105 can be used with a printed circuit board 105 if desired. The printed circuit board 100 must be configured to provide a plurality of PIC holes 104 beneath each of the programmable interconnect chips 105 utilized on the PC board 100. But with this change the structure of this invention can be made even more flexible and versatile than is possible with just one programmable interconnect chip 105.

As shown in Figure 3a a plurality of programmable interconnect chips 301-1 through 301-7 are utilized on PPCB

300. Typically, programmable PC board 300 is a multilayer PC board although in certain simple configurations a single layer programmable PC board can be used. Each chip 301-j (where j is an integer represented by $1 \leq j \leq J$) comprises a local programmable interconnect chip. A selected number of pins on chip 301-j are designated to electrically connect to the conductive traces in a bus formed on the programmable PC board 300 to interconnect that programmable interconnect chip 301-j to an adjacent programmable interconnect chip 301 such as chip 301-(j+1). Thus, in Figure 3a, programmable interconnect chip 301-1 is capable of interconnecting any one of a plurality of electronic components (not shown) mounted on PC board 300 adjacent to PIC 300-1 with another of that plurality of electronic components. In addition, programmable interconnect chip 301-1 is also able to connect these electronic components by means of buses 303-1 and/or 303-5 to the electronic components connected to adjacent programmable interconnect chips 301-2 and 301-5, respectively. Typically, busses 303-1 and 303-5 contain eight communication channels (i.e. eight traces) or 16 communication channels or data paths (i.e., 16 traces). Of course, these data busses can contain any number of transmission channels desired depending upon the requirements of the circuitry. The particular data busses 303-1 and 303-5 are formed by means of conductive traces formed on a selected surface of PC board 300. Similarly, programmable interconnect chip 301-2 is connectable to programmable interconnect chip 301-3 and 303-4 by means of conductive busses 303-2 and 303-4, respectively. Conductive busses 303-2 and 303-4 have the same characteristics as conductive busses 303-1 and 303-5 previously described and thus will not be described in detail. Likewise, conductive busses 303-3, 303-6, 303-7 and 303-8 interconnect selective programmable interconnect chips. Thus, conductive bus 303-3 interconnects programmable interconnect chip 301-3 to programmable interconnect chip 301-7. Conductive bus 303-7 interconnects programmable interconnect chip 301-4 to programmable interconnect chip 301-6. Conductive bus 303-6

interconnects programmable interconnect chip 301-5 to programmable interconnect chip 301-6 and conductive bus 303-8 interconnects programmable interconnect chip 301-6 to programmable interconnect chip 301-7. Conductive busses 303-3 and 303-6 through 303-8 each have the same characteristics as described above in conjunction with conductive busses 303-1 and 303-5 and thus this description will not be repeated. The structure of Figure 3a allows any electronic components on the PPCB to be interconnected with any other electronic component on the PPCB through one or more PIC's.

Figure 3b illustrates a second type of interconnect system wherein programmable interconnect chips 311-1, 311-2, 311-3, and 311-4 are interconnected by means of conductive busses 313-1 through 313-6. Thus, each programmable interconnect chip 311-1 through 311-4 shown in Figure 3b is connected directly to an adjacent programmable interconnect chip 311 by means of a dedicated conductive bus 313. For example, programmable interconnect chip 311-1 can be connected directly to programmable interconnect chips 311-2, 311-3 or 311-4 by means of conductive busses 313-1, 313-5 or 313-4, respectively. Each of these conductive busses contains a selected number of conductive lines (such as 8 or 16 conductive lines) implemented by means of 8 or 16 traces formed on a particular surface of programmable interconnect chip 300. Similarly, conductive busses 313-6, 313-2 and 313-3 have 8 or 16 conductive paths represented by traces formed on the PC board 300 and interconnect pairs of the programmable interconnect chips as shown in Figure 3b. The advantage of the structure shown in Figure 3b over the structure shown in Figure 3a is that each programmable interconnect chip 311 is able to communicate directly to each of the other programmable interconnect chips 311 on the printed circuit board 300. Of course, each programmable interconnect chip 311 also interconnects a plurality of electrical components such as integrated circuits or discrete devices inserted into the programmable PC board in the area adjacent to the programmable interconnect chip

311. Thus, programmable interconnect chip 311-1 interconnects electronic components (not shown) formed in the upper left quadrant 300-1 of programmable PC board 300. Programmable interconnect chip 311-2 interconnects electronic components (not shown) inserted into the programmable PC board 300 in upper right quadrant 300-2. Programmable interconnect chip 311-3 interconnects electronic components (not shown) inserted into the programmable PC board 300 in the lower right quadrant 300-3 and programmable interconnect chip 311-4 interconnects electronic components (not shown) inserted into the lower left quadrant 300-4 of programmable PC board 300. Thus the structure of Figure 3b is capable of electrically interconnecting the electronic components within each quadrant not only among themselves but also to the electronic components in other quadrants of the programmable PC board 300. The structure of Figure 3b thus gives great flexibility to the circuit designer in locating the electrical components to perform a given system function.

Figure 3c illustrates a bus configuration wherein a central bus 323-10 is formed on PC board 300 and programmable interconnect chips 321-1, 321-2, 321-3, 321-4, 321-5 and 321-6 are connected by means of conductive busses 323-1, 323-2, 323-3, 323-4, 323-5 and 323-6, respectively, to central conductive bus 323-10. Central bus 323-10 is formed by placing conductive traces on printed circuit board 300. Conductive busses 323-1 through 323-6 are similarly formed by placing conductive traces on the PC board. PC board 300 in general is a multilayer PC board with two or more layers of conductive traces. The structure shown in Figure 3c requires the traces making up bus 323-10 to be formed on one layer of PC board 300 and the traces comprising conductive busses 323-1 through 323-6 to be formed on a second layer. Electrical contact is then made between selected ones of the traces comprising busses 323-1 through 323-6 to the traces comprising bus 323-10 by means of holes, each hole electrically contacting the two or more traces to be interconnected.

The structure of Figure 3c simplifies the interconnections of the programmable interconnect chips 323-1 through 323-6 and improves the speed of interconnection of the common global bus signals but requires the establishment of a protocol for use of bus 323-10. Bus protocol is handled in a manner well known in the art by the programmable interconnect chips 321-1 through 321-6.

An additional interconnect structure is shown in Figure 3d. Here, programmable interconnect chips 331-1, 331-2, 331-3, 331-4, 331-5, 331-6 and 331-7 are interconnected by means of busses 333-1, 333-2, 333-3, 333-5, 333-6 and 333-7 all of which emanate from or go to central programmable interconnect chip 331-4. Chip 331-4 is primarily or exclusively dedicated to interconnecting the programmable interconnect chips 331-1 through 331-3 and 331-5 through 331-7. If desired and if the pins are available on programmable interconnect chip 331-4, programmable interconnect chip 331-4 also interconnects electronic components mounted on the programmable PC board particularly in the regions electrically adjacent to programmable interconnect chip 331-4. Each of the programmable interconnect chips 331-1 through 331-3 and 331-5 through 331-7 interconnects electronic components mounted on the PC board in areas adjacent to the programmable interconnect chip and has a certain number of pins (depending upon the number of conductive paths in each of busses 333-1 through 333-3 and 333-5 through 333-7) dedicated to interconnecting itself, through PIC 331-4, to other programmable interconnect chips 331. The advantage of the structure in Figure 3d is that programmable interconnect chip 331-4 can be configured to control the protocol for communication between each of the other programmable interconnect chips 331-1 to 331-3 and 331-5 to 331-7 and to improve the speed of the random global interconnections between the non-adjacent programmable interconnect chips.

Figure 4a illustrates a programmable printed circuit board 400 of this invention containing a number of different structures for both physically and electrically connecting

the electronic components to the programmable PC board 400. In the upper left hand corner of Figure 4a, an electronic component is capable of being inserted into sockets in the PC board such that leads on the component's package electrically connect to and are physically retained by component electrically conductive holes (such as component hole 402-1,1) in the PC board. The holes are shown formed on a standard grid pattern such that one type of programmable PC board can be used regardless of the circuit function to be performed. This type of component hole, called a socketed PCB configuration, allows the electrically conductive pins on component packages to be inserted into the component holes 402 in the PC board 400 and also to be removed from these component holes 402 (such as hole 402-1,1) without destroying the package pins.

The lower left portion of PC board 400 has been configured to contain electronic component packages which are soldered into the programmable PC board 400. Typically, component holes, such as hole 402-R,1, are also used in this configuration and the holes can be placed in the board in accordance with the pin configuration of the electronic component packages to be mounted in the board. Thus one row of holes (row R-1) is shown omitted from the PC board in the lower left hand corner. The disadvantage of soldering components to the PC board is that the components cannot be easily removed. The advantage, of course, is greater structural integrity, lower cost and higher reliability. Soldered PC boards are commonly used in production to ensure high reliability and quality and lower cost in the resulting product.

The lower right hand corner of the PC board 400 in Figure 4a comprises a solder pad configuration for the mounting of electronic components on the programmable PC board. As shown in Figure 4c, each pad, such as pad 402P-R,C, is connected by an electrically conductive lead, such as lead 407-R,C in Figure 4c to a component hole (such as hole 402-R,C in Figure 4c) in the PC board to which a trace (not shown in Figures 4a or 4c but the same as trace 103-R,C

shown in Figure 1a) is electrically attached for connecting that component hole to a corresponding PIC hole (such as hole 104-R,C in Figure 1b) connected to programmable interconnect chip 405 on the programmable printed circuit board. The solder pads can be formed on programmable PC board 400 in accordance with the connection configuration of the components to be mounted on the board, such as surface mounted devices.

Figure 4b shows an end view of the structure shown in top view in Figure 4a. Of importance, the socketed PC board can use an adaptive socket 407 of a type commonly known in the industry. For instance, appropriate sockets are produced by Augat Interconnection Systems of 40 Perry Avenue, Attleboro, Massachusetts 02703 and are disclosed in Chapter 7 of revision 5.0 of their July 1987 Engineering Design Guide.

Figure 5 illustrates a single programmable interconnect chip 505 placed on the center of programmable PC board 500. Electronic components 506-1 through 506-4 are mounted at various places on the programmable PC board 500 and are interconnected by conductive traces, shown schematically as 503-1, 503-2, 503-3 and 503-4, to programmable interconnect chip 505. Programmable interconnect chip 505, however, has two busses extending from it to ports on the edge of the printed circuit board. These ports comprise a test port 508 for the transmission of test signals from an external source such as a computer to programmable interconnect chip 505 to test the state of each conductive trace 503 coming into programmable interconnect chip 505 and a control port 509 for allowing control signals from an external source such as a computer to be transmitted to programmable interconnect chip 505 to control the configuration of programmable interconnect chip 505. The two ports 508 and 509 can be actuated simultaneously such that the computer can determine that the proper signals are present on selected traces connected to PIC 505 during the configuring of PIC 505 and during the operation of the system represented by FPPCB 500 and the attached electronic components 506-1 through 506-4

and PIC 505.

In general, the interconnection of one trace on the programmable PC board to another trace can be carried out in accordance with any one of a number of different architectures. | Figures 6a and 6b illustrates a programmable interconnect chip 605 in accordance with this invention suitable for implementing the programmable interconnect function in the structures described above. In Figure 6a the programmable interconnect chip 605 contains a plurality of cells 606-1,1 through 606-S,T where S represents the number of rows of cells in the programmable interconnect chip 605 and T represents the number of columns cells in chip 605. Each cell has an array of electrically conductive pads 607-1,1 through 607-M,N where M represents the number of rows of pads in the cell and N represents the number of columns of pads in the cell. Since each cell is identical in configuration, only the conductive pads 607 associated with cell 606-1,1 will be described in detail with the understanding that the conductive pads associated with each of the other cells 606-s,t (where s is an integer given by $1 \leq s \leq S$ and t is an integer given by $1 \leq t \leq T$) in chip 605 function identically.

Figure 6b illustrates the configuration of cell 606-1,1 and also of each of the other cells 606-s,t. In Figure 6b horizontal conductive tracks 608-1 through 608-J (where J is an integer representing the maximum number of horizontal conductive tracks formed on programmable interconnect chip 605) are shown. In addition, vertical conductive tracks 609-1 through 609-K are shown where K is an integer representing the maximum number of columns of conductive tracks formed on programmable interconnect chip 605. The horizontal conductive tracks 608-1 through 608-J are formed on one level of interconnections on chip 605 while the vertical conductive tracks 609-1 through 609-K are formed on a second level of interconnections on chip 605. Typically, these interconnections are formed in a manner well known in the semiconductor processing arts and thus the method of forming these interconnections will not be discussed. The

horizontal conductive leads 608-1 through 608-J have differing lengths across the chip. The cell 606-1,1 shown in the upper left hand corner of both Figure 6a and Figure 6b has a plurality of horizontal conductive leads 608 originating in and extending from cell 606-1,1 to each of the other cells 606-1,2 through 606-1,T in the same row. Likewise, cell 606-1,1 has a plurality of vertical conductive leads 609 extending from cell 606-1, 1 to each of the other cells 606-2,1 to 606-S,1 in the same vertical column.

The horizontal and vertical traces 608 and 609 have at each of their intersections a programmable connective structure such as for example, an antifuse. Typically, an antifuse comprises a capacitive structure with a dielectric capable of being broken down by the application of a selected voltage to provide a conductive path between the two plates of the capacitor. Antifuses are well known in the art and thus will not be described in detail. Other kinds of programmable elements can also be used depending upon design considerations. The substrate of the programmable interconnect chip 605 has formed in it selected transistors to enable the programming of the antifuse elements at selected intersections in accordance with design requirements.

As shown in Figure 6b, vertical leads 609-1 through 609-K are formed on the programmable interconnect chip 605 so as to extend at a minimum across one cell 606 and at a maximum across all cells. Thus a plurality of vertical leads 609 cross each cell with the length of leads varying from being such as to extend across just that cell to being such as to extend across all cells in a column.

Horizontal conductive leads 608-1 through 608-J likewise extend across the programmable interconnect chip 605. Again, the horizontal leads 608 extending across one cell vary in length such that they extend across only that one cell up to a length which will extend across all cells. In Figure 6b, breaklines are included to indicate that the semiconductor chip 605 is only partially shown with

interior portions of the chip having been removed for clarity. However, some conductive leads break not because of the breaklines showing removal of semiconductor material but rather because the conductive leads are intended to stop at a given point. Small lines 618-1, 618-2 and 618-3 are drawn at the terminal points of a conductive lead perpendicular to that lead to indicate that the conductive lead is intended to terminate at those points. A horizontal conductive lead thus might comprise one conductive segment each extending across the whole chip 605 or a plurality of conductive segments extending across a section of the chip. Similarly, the vertical conductive leads likewise vary from one conductive lead which will extend across the entire height of the chip or two or more conductive segments each extending across a selected portion of the chip.

The particular configuration of the conductive leads extending across one cell and from that cell to adjacent cells depends upon an analysis of the electrical functions to be carried out by the programmable printed circuit board and is selected using the most probable types of system requirements to be imposed on programmable interconnect chip 605. This selection depends upon an analysis of the circuit functions to be performed by the programmable printed circuit board of this invention and thus the actual configuration of the programmable interconnect chip is determined in light of the proposed uses for the programmable printed circuit board.

To interconnect a given lead corresponding for example to the lead 609-1 connected to pad A in cell 606-1,1 to a given lead corresponding to a different pad either in cell 606-1,1 or in some different cell using the structure shown in Figure 6b, an interconnection between the appropriate vertical conductor 609 and the appropriate horizontal conductor 608 is formed. For example, to connect pad A to pad B (both in cell 606-1,1) the intersection of vertical lead 609-1 and horizontal lead 608-1 is programmed by applying a high voltage to this intersection in the circuit so as to break down the dielectric between these two points

and form a conductive path therebetween. In addition, the intersection of vertical conductor 609-4 and horizontal conductor 608-1 is also subjected to a high voltage to break down the insulation between these two leads to form an additional conductive path between these two leads. Thus, pad A is connected to pad B by conductors 609-1, 608-1 and 609-4. Should it be desired to connect pad A to any other lead or pad then pad B will also be connected to that other lead or pad. However, such a connection must be compatible with the circuit in order to be made.

Figure 6b also illustrates the particular connections which must be formed to connect pad A to pad D, pad A to pad C or pad A to pad E. Should all of these connections be made then pads B, D, C and E will also be connected to each other through pad A.

Figure 6c illustrates a programmable interconnect chip 605 utilizing a single cross-point switch matrix array. When the number of pads to be interconnected is quite small (e.g., on the order of 100 to 300) then the structure of Figure 6c has certain advantages of simplicity and ease of fabrication. The structure shown in Figure 6c is simpler than that shown in Figure 6b in that each pad (such as pad A) is connected by a conductive trace (such as conductive lead 625-A) permanently to a vertical conductive lead (such as lead 629-1. In addition, vertical conductive lead is permanently connected by via 624-1 (as shown by the solid dot) to horizontal conductive line 628-1. Should it be desired to connect pad A to any other pad accessible by a vertical lead 629 passing over or under horizontal lead 628-1, the circuit is programmed by applying a voltage at the correct node (such as node 623-1) to form a conductive path between devised vertical and the horizontal leads (such as horizontal lead 628-1 and vertical lead 629-4) thereby to connect pad A to pad B. Pad B is connected to vertical lead 629-4 by conductive trace 625-B. Note that each vertical line is permanently connected to one horizontal line 628 by a via (such as via 624-1). This greatly simplifies the interconnection required to program the printed circuit

board of this invention since one pad can be connected to another by only one programming element. However, as the number of pads become large, this particular structure becomes relatively inefficient in its use of space on the programmable interconnect chip 605. The total number of programming elements required equals the number of pads squared.

Figure 6d shows a variation of the structure in Figure 6c. Using the structure of Figure 6d to interconnect pad A (which connects to a PIC hole such as hole 104-1,1 shown in Figure 1b) to pad D (which connects to a similar PIC hole 104) two programming elements must be programmed. Thus, the element at the intersection of vertical lead 639-1 and horizontal lead 638-1 must be programmed as must the element at the intersection of vertical lead 639-(K-1) and horizontal lead 638-1. However, as shown in the structure of Figure 6d, each conductive pad such as pad A or pad D is connected by means of a conductive trace such as trace 635-A to a vertical lead 639. The number of horizontal lead is in this embodiment, less than 1/2 the number of vertical leads because as each horizontal lead connects two pads whereas each vertical lead is connected directly to one pad only. Thus, the structure 6d has greater flexibility than that shown in Figure 6c at the price of two programming elements per connection rather than one. The number of programming elements is 1/2 the square of the number of pads. As the number of pads become larger (for example above 200 to 500 pads) this structure becomes relatively inefficient.

Figure 6e illustrates the single switch cross-point matrix array of Figure 6c with interconnections formed to connect pad 1,1 to pad 4,1. To do this, the intersection of the vertical lead $V_{1,1}$ and the horizontal lead H_1 is programmed as is the intersection of the vertical lead $V_{4,1}$ and horizontal lead H_1. Thus, two elements have been programmed to connect pads 1,1 and 4,1. To connect pad 1,2 to pad 4,4, the programming elements at the intersection of the vertical lead $V_{1,2}$, and the horizontal lead H_3 and of the horizontal lead H_3 and the vertical lead $V_{4,4}$ are

programmed. Note that as a convention in Figure 6e, wherever the intersection of a vertical and a horizontal lead are not shown to be electrically connected by a solid dot, a programmable element (often shown by a hollow circle) will be present even though a hollow circle is not shown at such intersection.

Figure 7a shows in block diagram form the architecture of the programmable interconnect chip 605. The interior 605a of chip 605 contains the cells 606 (as described in conjunction with Figures 6a through 6e) and the horizontal and vertical tracks 608 and 609 respectively. In peripheral area 605b which forms an annular square around interior 605a are placed control and programming circuits including shift registers for selecting particular horizontal and vertical tracks the intersections of which are to be programmed. In addition, buffer circuitry for the testport bus and the control port bus are provided in this region of chip 605. Annular region 605c surrounds annular region 605b and contains additional circuitry essential to the operation of the chip such as mode selection circuitry which will determine whether the programmable interconnect chip is in the test mode, the operating mode or the programming mode. Additional special circuitry as required will also be placed in peripheral region 605c.

Figure 7b illustrates a programming structure and particularly programming transistors and circuits to select the intersection to be programmed of horizontal and vertical conductive leads on the programmable interconnect chip using only two transistors in the programming circuit path. Utilization of the structure shown in Figure 7b allows the programming current to reach into the hundreds of milliamps to amperes range necessary to break down the dielectric between the vertical and horizontal conductive leads to form an interconnection therebetween with sufficiently low resistance. For example, to program the intersection of vertical conductive track V_1 and horizontal conductive track H_1, transistors Q1 and Q2 are provided. Transistor Q1 has its gate connected to voltage source VGP_1 and transistor Q2

has its gate connected to a voltage source HGP_1. The source of transistor Q1 is connected to vertical conductive track V1 while the drain of transistor Q1 is connected to conductive lead VDP_1. The source of transistor Q2 is connected to horizontal lead H_1 and the drain of transistor Q2 is connected to conductive lead HDP_1. To program the intersection of vertical lead V_1 and horizontal lead H_1, VGP_1 is applied to take the gate of Q1 to a high voltage V_{GH}, the gates of other transistors in the array such as transistor Q3 is held at zero volts and the drain voltage VDP1 on transistor Q1 is taken to V_{PP}. However, the gate voltage of Q4 is taken high because HGP_1 is taken to a high voltage to turn on transistor Q2. However, the voltage on the drain of Q2 is taken to zero volts by driving HDP_1 to zero and HDP_2 which applies to the drain of Q4 is taken to zero or to V_{PP} over 2 (which voltage is selected so as not to program the programming element at the intersection of V_2 and H_2. V_{PP}, the programming voltage, is typically 15 to 50 volts. V_{GH}, which is applied to lead VGP_1, is larger than V_{PP} by the transistor threshold voltage and thus is approximately 18 to 53 volts. Because the devices Q1 to Q4 operate under high voltage, the threshold voltage of these transistors is made approximately 3 volts. As a result of the above-described voltages, only the programming element at the intersection of conductive lead segments H1 and V1 will receive the full programming voltage V_{pp} and break down.

Figure 7c shows a bidirectional amplifying circuit capable of amplifying signals coming in either direction depending upon control signals applied to the input and output buffers contained within the circuitry. Thus, as shown in Figure 7a, each pad on PIC 705 is connected to a special function test line (illustrated in Figure 7c) and the special function test line is then capable of being connected to the test port by turning on the output buffer through a high level signal applied to the lead labeled S on the output buffer together with a high level enable signal applied on the terminal labeled E. Simultaneously with the

application of a high level signal on the lead labeled S to the output buffer, a low level signal is applied to the lead labeled $\overline{S}$ to the input buffer thereby turning off the input buffer. Reverse polarity signals applied to terminals S and $\overline{S}$ result in the input buffer turning on and the output buffer turning off thereby allowing a signal from the test port to be applied to the pad. The S and E signals are transferred to the peripheral circuits in annular region 605B of Figure 7a to select the pads on the PIC and the leads of the components on the FPPCB to connect to the test port.

Figures 8a and 8b illustrate structures for attaching the program interconnect chip such as chip 105 in Figure 1a to the PC board 100. Figure 8a illustrates a program interconnect chip contains pads with metal bumps shown in an exploded view above the PIC holes (corresponding to holes 104-1,1 through 104-R,C shown in Figure 1b). A buffer medium comprising an elastomeric material which under pressure will conduct in the vertical direction but not the horizontal direction, is shown placed between the program interconnect chip and the PIC holes. The buffer medium could also be a carrier using button springs of a type well known in the art. This medium is a good buffer between the surface of the PIC and FFPPCB with their different surface flatness and temperature coefficient. The particular structure to be used to attach the programmable interconnect chip to the programmable PC board will depend upon the design requirements for the particular system utilizing the combination of programmable PC board and programmable interconnect chip and cost considerations.

Figure 8b shows an alternative structure for attaching the programmable interconnect chip such as chip 105 in Figure 1a directly to a programmable printed circuit board such as board 100 in Figure 1a. In Figure 8b, the programmable interconnect chip has formed on one surface thereof a conductive pad to serve as an interface between a conductive element on the chip and a metal bump consisting of a soft solder such as lead tin placed on a nickel bottom

layer. Alternatively, the whole bump is made of indium. The nickel is used to give strength to the bump. The programmable PC board has solder formed in the PIC hole so as to form a bump on the surface of the PC board to which the programmable interconnect chip is to be attached. The PIC hole such as hole 104-r,c in Figure 1b, is plated typically with copper to a selected thickness such as 1 mil. The solder bump will, when the programmable interconnect chip is brought into pressure contact with the solder and the combined structure heated, form a solid contact with the metal bump. The two materials will wet and become one thus firmly securing and electrically connecting the programmable interconnect chip to the programmable printed circuit board. Solder bumps are well known in the art and thus this structure will not be described in greater detail. Other structures can be used to attach the programmable interconnect chip such as chip 105 in Figure 1a directly to a programmable printed circuit board such as board 100 in Figure 1a. Such structures include attachment of the PIC on the board and wire bonding of the pads on the PIC to the PIC holes. Any other structure known in the art to attach electronic components to a printed circuit board can be used with this invention and the structures described for this purpose are exemplary only.

In an alternative embodiment of this invention, a printed circuit board comprises a first portion containing conductive traces for interconnecting electronic components formed thereon without the use of a programmable integrated circuit and a second portion containing at least one programmable integrated circuit for interconnecting electronic components formed on at least the second portion of the printed circuit board. Electronic components formed on the second portion of the printed circuit board are in some cases interconnected with the electronic circuit formed on the first portion of the printed circuit board by conductive traces. These conductive traces typically will run from the first portion of the printed circuit board to at least one programmable integrated circuit for

interconnecting electronic components formed on the second portion of the printed circuit board, thereby to electrically connect the second portion of the printed circuit board to the first portion of the printed circuit board.